


INSTALLATION

JANGAL
the green way

You have decided to buy our Modular Wall - Moos and now you want to install it.
We recommend the following two mounting options.




Tool which is needed.

- Rubber gloves
- folding rule
- Pencil / Felt pen
- Drill and dowel
- Cordless screwdriver
- Spirit level
- Cutter or scissors




Wear gloves!

The moss can release its color when touched. Use gloves for assembly or wash your hands immediately afterwards to avoid soiling other objects.




Storage

Never store the packages upright, but lying flat on a level surface to avoid deformation.




Gluing

We recommend a solvent-free mounting adhesive. However, the selection of the appropriate adhesive always depends on the substrate. The adhesive is applied in spots or in serpentine lines on the back. Adjust the panels using a spirit level and apply pressure to attach them.



Screwing


For mounting you need 4 screws per element, evenly spaced and matching the color of the felt. Screw through the felt. Draw the holes in advance.



Ceiling mounting

Fastening to the ceiling is done exclusively with screws. It is recommended to use 4 screws per panel, evenly placed and matching the color of the felt. Attach the screws through the felt and adjust the panels using a spirit level for correct alignment.


MULTIPLE DESIGNS AND COMBINATIONS WITH OTHER FORMATS POSSIBLE, FOR EXAMPLE:



Note

Please avoid prolonged exposure to sunlight or light exposure, for example from LED or halogen spotlights at a short distance. Prevent excessively high humidity (>70%) as well as very dry air. Although our moss is extremely natural, watering or spraying is not or spraying is not necessary.

Our mosses are made of purely natural materials, so occasional changes may occur, such as color changes, lichenification or growth. Please do not hang them near fireplaces, heaters or other heat sources under any circumstances. Follow these instructions to avoid premature color loss of the products.



jangal.eu